

Model 1316S

Miter Head Bandsaw

True Swivel Head Mitters to 60 Degrees
13" Capacity



**WELLSAWS work harder and last longer
because they are built better.**

Wellsaw®

2829 N. Burdick St.
Kalamazoo MI 49004
Phone: 269-345-1132
Fax: 269-345-0095
www.wellsaw.com



Model 1316S Miter Head Bandsaw

Manufactured in the United States of America

Standard Features:

Saw Head Swivels on Precision Ball Bearings
Miter to 60° No need to swivel the stock
Large Protractor for Accurate Angle Selection
5 ft. x 18 in. Infeed Roller Conveyor
Spring Loaded Carbide Guides with Rollers
Combination Reduction Gearbox and
Ring & Pinion Blade Drive
Baldor® Motor
 3 HP Motor 3 Phase TEFC
 2 HP Single Phase ODP
Infinitely Variable Blade Speeds
Variable Hydraulic Downfeed Control
Work Light w/ Transformer
Rite-Tension® Blade Tensioning Device
Wet Cutting System w/ Full Surround pan
Powered Blade Brush
110 Volts at Controls
Magnetic Starter w/ Overload and Undervoltage
 Protection
Precision Ground Bed and Vise Jaws
Quick Acting Vise
Adjustable Stock Stop/Back Gauge
Auto Shut-Off at End of Cut
OSHA Blade Guarding
Tiger-Tooth® Bi-Metal Blade
Coolant for Initial Start-Up

Specifications:

Capacity:	Round	Rectangular
@ 0° (90°)	13"	13"H x 16"W
@45°	11-1/2"	13"H x 11-1/2"W
@60°	8"	8-1/2" H x 8"W
Blade Size	1" x .035" x 12'- 6" (150")	
Blade Speeds	Infinitely Variable 70 - 375 SFPM	
Blade Guides	Carbide Guides with Rollers	
Blade Tension	Manual Rite-Tension®	
Electrical Options	115-208-230/60/1 208-230-460/60/3	
Coolant System	Tank Capacity 8 gallons Submersible Pump 115V/ .6 Amp/ 3 gpm	
Vise Control	Quick Acting / Manual Screw	
Feed Rate Control	Variable Hydraulic	
Band Wheels	15" Diameter Cast Iron	
Stock Stop Projection	25"	
Bed Height	35"	
Floor Area	90"W x 76"L	
Shipping Weight	1600 lbs.	

Factory Installed Options Available

PLC controlled Semi-Automatic Operation
Blade Break/Stall Switch
Flush Hose w/ 8.5 gpm Pump
Powered Frame Raise and/or Powered Vise
Laser Line Pointer
Casters (Set of 4, 2 Locking)
NFPA Electrics (w/disconnect)
Stock Stand, 18"
5 ft. Non-Powered Roller Conveyor
10 ft. Non-Powered Conveyors
Please Contact Our Factory For Additional Options

Specifications Subject to Change Without Notice

Wellsaw®

2829 N. Burdick St.
Kalamazoo, MI 49004
Phone: 269-345-1132
Fax 269-345-0095
Email: info@wellsaw.com